

NEW ITEM RELEASE

Date : Aug. 28, 2023

LA23601-1PS-TTL (White Laser Module Series, Model I / Full module type)

Page : 1/3

Specification Characteristics

- Model No : LA23601-1PS-TTL
(產品型號)
- Operating Voltage : 12 VDC
(工作電壓)
- Operating current : 1.6±0.1A @ 25°C
(工作電流)
- Fiber output luminous flux : 240lm min.
(光纖出口光通量)
- Color Temperature : 6000K
(色溫)
- ESD (Human Body Model) : 2KV
(防靜電)
- Fiber Spec. : Core Diameter : 1,000 um, Connector : SMA905
(光纖規格) (芯徑) (接口)
- Fiber Length : 2 Meters
(光纖長度)
- Operating temperature range : -20 ~ +50°C
(操作溫度範圍)
- Functions of the button
(按鍵功能)

NEW ITEM RELEASE

Date : Aug. 28, 2023

LA23601-1PS-TTL (White Laser Module Series, Model I / Full module type)

Page : 2/3

A. After power on, the module will be in outside control mode, you can input the control signal by an X1.25 plug connecting cable to control output enable/disable output frequency.

(輸入電源後，模組為外部調控模式，透過 X1.25 訊號線控制輸出亮、暗的頻率)

B. To press the button, the module will change to continue output mode.
(短按長亮。)

C. Press the button again, the module change to be in pulse output mode. On/off frequency is in 0.5Hz / 50mS.

(再次短按，進入內部調製模式，亮/暗頻率為 0.5Hz / 50ms)

D. Press the button again, to turn off the module.
(再次短按，關機)

Note : Outside control method : By an X1.25 plug connecting cable, the yellow wire is TTL control signal input cable, the black is ground wire.

(註：外部控制方式：使用 TX1.25 型連接插頭線，黃線為 TTL 調製信號，黑線為 GND。)

NEW ITEM RELEASE

Date : Aug. 28, 2023

LA23601-1PS-TTL (White Laser Module Series, Model I / Full module type)

Page : 3/3

Dimension

